



Donaldson.
FILTRATION SOLUTIONS

DATA SHEET

Filter media

High Efficiency Polyester Anti-Static

High Efficiency Polyester Anti-Static

Appearance	Grey, uncorrugated
Use	Pleatable filter media
Composition	Spunbond polyester aluminised
Area weight	260 g/m ²
Thickness	0.61 mm
Air Permeability (Frazier)	360 m ³ /m ² .h at 125 Pa
Surface electrical resistance (DIN 54345)	Less than 10 ⁸ Ω (on the aluminised size)
IFA/BIA certificate (DIN 660335-2-69)	Class M
Temperature (dry heat)	
Continuous	93 °C
Peaks	110 °C
Chemical resistance	
Hydrolysis	N/A
Acids	Good
Alkalies	Good
Oxidising agents	Good
Organic solvents	Good
Abrasion resistance	Excellent
Supports combustion	Yes
Application field	Wide pleat spacing provides excellent particle release. Highly recommended for chemical, food, and industrial processing when product contamination must be minimized. Excellent performance on moist, hygroscopic or agglomerative dust.

Order online



shop.Donaldson.com

Contact us

Donaldson.com

Publication DOCAM0532501 • Rev. 11 • 1118

Donaldson reserves the right to change or discontinue any model or specification at any time and without notice. Freedom from patent restrictions must not be assumed.