



Donaldson.  
FILTRATION SOLUTIONS

## DATA SHEET

### Filter media

High Temperature

## High Temperature

<b>Appearance</b>	Yellow, corrugated
<b>Use</b>	Pleatable filter media
<b>Composition</b>	Combination of two High Temperature synthetic fibers
<b>Area weight</b>	130 g/m <sup>2</sup>
<b>Thickness</b>	0.45 mm
<b>Air Permeability</b> (Frazier)	275 m <sup>3</sup> /m <sup>2</sup> .h at 125 Pa
<b>Surface electrical resistance</b> (DIN 54345)	N/A
<b>Temperature (dry heat)</b>	
Continuous	177 °C
Peaks	200 °C
<b>Chemical resistance</b>	
Hydrolysis	Good
Alkalies	Good
Oxidising agents	Good
Organic solvents	Good
<b>Abrasion resistance</b>	Excellent (TAPPI 476 Taber method)
<b>Supports combustion</b>	No
<b>Application field</b>	Specially designed for dry, high temperature applications. Very good choice for metallurgical, chemical, and industrial applications  Metallurgical, chemical processing and industrial applications

Order online



[shop.Donaldson.com](http://shop.Donaldson.com)

Contact us

[Donaldson.com](http://Donaldson.com)

Publication DOCAM0846001 • Rev. 00 • 0225

Donaldson reserves the right to change or discontinue any model or specification at any time and without notice. Freedom from patent restrictions must not be assumed.