



Donaldson.  
FILTRATION SOLUTIONS

## DATA SHEET

### Filter media

Polyester + PTFE Coating

### Polyester + PTFE Coating

<b>Treatment</b>	PTFE Coating
<b>Use</b>	Pleatable filter media
<b>Composition</b>	100% Polyester
<b>Area weight</b>	245 g/m <sup>2</sup>
<b>Thickness</b>	0.55 mm
<b>Air Permeability</b>	550 m <sup>3</sup> /m <sup>2</sup> /h at 200 Pa
<b>Surface electrical resistance (Ohm)</b>	<10 <sup>6</sup>
<b>IFA/BIA certificate (DIN EN 60335-2-69:2015)</b>	M
<b>Temperature (dry heat)</b>	
Continuous	120 °C
Peaks	140 °C
<b>Chemical resistance</b>	
Oil/Water	Very Good
Hydrolysis	Good
Acid	Good
Alkali	Fair
<b>Dust release</b>	Excellent

Order online



[shop.Donaldson.com](http://shop.Donaldson.com)

Contact us

[Donaldson.com](http://Donaldson.com)

Publication DOCAM06599N • Rev. 01 • 0319

Donaldson reserves the right to change or discontinue any model or specification at any time and without notice. Freedom from patent restrictions must not be assumed.