



Donaldson.
FILTRATION SOLUTIONS

DATA SHEET

Filter media

Sintered Polyethylene

Sintered Polyethylene

Appearance	Black
Use	Sintered panels
Composition	Sintered polyethylene composite material
Area weight	2.6 to 2.9 kg/m ²
Thickness	4 mm
Air Permeability (DIN 53887)	1.21 m ³ /m ² /min@200Pa
Dimensional stability at 60°C (%)	< 1.0
Surface finish	PTFE emulsion coating
Additional treatments	N/A
Surface electrical resistance (DIN 54345)	N/A
IFA/BIA category (DIN 660335-2-69)	Class M
Temperature (dry heat)	
Continuous	70 °C
Peaks	70 °C
Chemical resistance	
Hydrolysis	Excellent
Acids	Very good
Oxidising agents	Good
Abrasion resistance	Excellent
Supports combustion	Yes
What to avoid	Can be degraded by strong oxidising agents such as nitric acid, bromine or chlorine etc. Some organic solvents such as toluene may cause swelling. Avoid very cohesive, sticky materials or moisture sensitive dusts which are likely to crust on the media surface. Also avoid those materials containing oils, fats and greases, etc.
Suitable applications	Sintered elements are suitable for the vast majority of chemical conditions likely to be encountered in Sintamatic applications. Any dust handled should be dry and free flowing, free from any oils, fats or greases etc.

Order online



shop.Donaldson.com

Contact us

Donaldson.com

Publication DOCAM0833501 • Rev. 00 • 1118

Donaldson reserves the right to change or discontinue any model or specification at any time and without notice. Freedom from patent restrictions must not be assumed.